# CASE STUDY

# NPO Saturn – Aero Engine Noise Certification

Russia Aerospace & Defence PULSE

Noise levels from individual aircraft are restricted by the noise certification requirements given in the Federal Aviation Regulations (FAR) Part 36, and the ICAO Convention on International Civil Aviation, Annex 16. NPO Saturn and Snecma turned to Brüel & Kjær for assistance for noise certification of their new engine. Brüel & Kjær responded with a state-of-the-art noise certification system supporting these regulations.

Photos courtesy of NPO Saturn







Aircraft engine manufacturer, NPO Saturn, was established on July 5, 2001 through the merger of Rybinsk Motors JSC and A. Lyulka-Saturn, a leading Russian aircraft engine design bureau. The company, founded by Pavel Aleksandrovich Soloviev, has its headquarters in the town of Rybinsk and holds a 50% stake in the PowerJet joint venture with Snecma.

NPO Saturn is the leading Russian designer and manufacturer of gas turbine engines for military and civil aviation, unmanned aerial vehicles, electric power plants, gas pumping units and marine applications. It sells its advanced gas turbine solutions mainly in the high-technologies market.

## **Aircraft Engine Noise Certification**

Sukhoi Superjet 100 regional aircraft



PowerJet, formed as a joint venture between NPO Saturn and French SNECMA (SAFRAN Group) in 2004, have designed and built the new SaM146 turbofan engine selected by the Sukhoi Civil Aircraft Company to power its Superjet 100 aircraft family. The Sukhoi Superjet 100 is a medium-haul airliner developed in collaboration with Alenia Aeronautica (Italy), and with consultancy support from Boeing (USA).

With this design went a commitment to the environment. The new engine should incorporate the most stringent noise and emissions standards using state-of-the-art eco-technology – "to meet or exceed current and future regulations".

Few aviation issues evoke as much interest and emotion as noise. Noise is considered the most important environmental concern for many people who live or work near an airport. Engine manufacturers like PowerJet are therefore making huge efforts to reduce their environmental impact and improve cabin comfort.

Noise levels from individual aircraft are restricted by the noise certification requirements given in the Federal Aviation Regulations (FAR) Part 36, and the ICAO Convention on International Civil Aviation, Annex 16. NPO Saturn and Snecma turned to Brüel & Kjær for assistance for noise certification of their new engine. Brüel & Kjær responded with a state-of-the-art noise certification system supporting these regulations.

## The PowerJet SaM146 Turbofan

The PowerJet SaM146 is a turbofan engine designed from the ground up to power regional jets. Snecma is in charge of the core engine, control system, transmissions, overall engine integration and flight testing. NPO Saturn is responsible for the components in the low-pressure section and engine installation on the Sukhoi Superjet 100 regional aircraft, and ground testing – including the noise certification.

Together Snecma and NPO Saturn have built a new Open-Air Test Bench in Poluevo (Russia, Yaroslavl region) to handle certification tests for the SaM146 and other engines. This test rig covers three types of testing – performance, certification operational tests, and noise certification of the propulsion system.



#### The Engine Noise Certification System

The certification system measurement control suite The purpose of the engine noise test is to predict the noise performance of final aircraft in flight for type approval, and to feed engine-specific noise signature, such as jet noise, fan noise and pure tones into noise simulation software.

The Brüel & Kjær Static Engine Certification Test system performs data acquisition and analysis for static engine certification testing. The system primarily uses COTS (Commercial Off The Shelf) products, providing a full engine noise measurement and analysis capability. Data acquisition is performed using Brüel & Kjær PULSE acquisition hardware, and real-time and post processing using the Brüel & Kjær PULSE LabShop software.



The system supports the industry standards and equivalent procedures set out in the certification standards Annex 16 and FAR 36 (Refs 1 and 2).

The system uses dedicated application-specific software, providing a streamlined workflow, thereby ensuring all required operations are performed to maximum efficiency. The parameter used to assess aircraft noise is the Effective Perceived Noise Level (EPNL) measured in EPN dB. This depends on the annoyance perceived by the ear, the tonal content of the spectrum, and the time for which the aircraft noise remains within 10 dB of the peak noise at the measurement position.

Sound Attenuation Correction for temperature and humidity is in accordance with ARP 866A.

#### What is Measured?

- Far-field and near-field microphones provide noise measurements
- · Tacho signals provide engine speed data
- Data acquisition modules provide acquisition and conditioning of the microphone and speed signals
- A weather station provides all necessary temperature, wind speed, wind direction, barometric pressure and humidity data
- An IRIG-B receiver provides time stamping of the data

#### How is the Data Handled?

• Acquisition and analysis workstations run the software to make the certification noise measurements and analysis



Validation workstations provide users with remote access to the live data acquired to provide independent validation of the measurement data

Dated	Level Haber A	92	· (Ter	(+30	W (THUT, 101, 106.)	0.01	W (THAT
sN77		Time((h27) - Input (Red)	Analyzer	Time((h00) - Input (Real	\ffT Analyzer	- Time(h0() - Input (Re	ta) \FFT Analyzer
sK19 sk11		(Pa)	Brian & Kiper - Br	(Pa) 4001		(Pa) 40m1	
1872		2014	- MA	2019-	Am A	2019-	Am de
1011		0 100 10	1	10%	A VI	2019-	2 VIV
+535		- WWWWW	W/	a starting of	M./	a sector	Mr. F
eN17		-30%		-2010	T	-20m 1 W	7
eA18		-00-		-65		-609-	
CM18		-50m	An The law The	-50ml	Man Man June Man	-50ml	Max Was have Was
aMI aM2			4		[4]		14
(M)							
		10.4	Con Charles	(aves	Cite Latitud	lave	Charlen Con
(56)		Time(204) - 2944 (Nat)	FFT Analyzer	Time(200) - 2quit (Nea	3 \ FFT Analyzer		2 gut (9xa) \ FFT dnal-par
-004 -005		Pw)		(Pa)		[48/Q9+P#]	
		200	MA A	30%	An A	50-	
MIT		10%		10m-	V		
a 511 a 512		- strain of the state	N/	and and the set		20 WK	
		-30%- W		-30% YV		10	al de
0 1000 2000 2000 4000 5000	100m 700m 000m 100m 1	-01		-67		o Which in	Jackson and the star
- Low		0 4n 0m 12n 1	ón 20n 24n 20n	0 4n 0m 12n	Men 20rs 24m 20m	0 4 8 1	13 19 29 24
Carlos Barris Carlos Ca			1		00		142
A STATE OF A		Last.	CTerT. (11. (75.)	Cont	CTer. 11. 01.	Last	ALL TRATIL AT L ONL
A and Capital		Time(:h)(:) - input (Pe#)	VIET Analyzer	Time(tHit) - Input (Real	\//// Analyzer	Time(\$42) - Input (%e	(e) \FFT Analyzer
In the second		50		Tel	1	4010-	and a state of the
		2019-	NA PO	2019	MM	2014	
and the		2 ka au	N 8	The way	MAY -	2010	1 want Mart
		10	N I	- Store - Charles	¥ .	200 Second	
		-30%		-30%		2010	
a m Car		-50%		-50%-		-001	
A DE CARTE AND A DE C		0 4n 8x 12n 3	6m 20m 2mm 28m	D 4n 8n 12n	16m 20m 24m 28m	D 4m 8m 32m	Man 20m 24m 28m
and the second se			4)		(4)		14
and part of the local data and the		(944	N .1ee. 1991.09.	(94)	C. Level. 161.7709975	-944	Cies. 1.61.7097
		140,00x Fe()	Brief & Kjer etc.	(4,0)+Ps)	ter least ( c. s.	[40,00x-Pa]	sthear formal (Co.a sometion C
and the second se		30					
		40		<sup>501</sup>		304	
and the second s		30		·			
and and		20 114					
		Websterners	an and she had not	~		~ · · · · · · · · · · · · · · · · · · ·	
- Con		and a state of the second s	and the fighted is	20		20	
and the second se		0 4 8 12 10	19 28 24	31.5 63 125 250 500	1 R R 4 R 19	11.5 60 125 250 5	10 12 22 46 18 152 1671

With complex measurement setups like these, getting the measurements right first-time is a must! In this specific case, real-time validation of 77 channels up to 25 kHz was provided on multiple screens.

Final reports are generated using predefined  ${\rm Microsoft}^{\otimes}\,{\rm Word}\,\,{\rm templates}.$ 

Roman V. Lubimov, General Design Deputy and Director of Building 7 says, "With the implementation of the SaM146 project, NPO Saturn was faced with the challenge of developing and implementing a complex measurement program using state-of-the-art

technology. This included a system for acoustic measurements based on the latest Brüel & Kjær solutions for noise certification testing".

Multi-channel display allows for real-time validation of measurements

Roman V. Lubimov, General Design Deputy and Director of Building 7



He continues, "With Brüel & Kjær, we experienced a company skilled in providing superior hardware and software, acoustic measurement solutions and the professional contractor services needed to supply this unique acoustic measurement system – fully complying with the requirements of the certification standards of Annex 16 and FAR 36. The presence of Brüel & Kjær's official representation in Russia had also a positive impact on the quality and timing of this project".

© Brüel & Kjær. All rights reserved.

HEADQUARTERS: Brüel & Kjær Sound & Vibration Measurement A/S · DK-2850 Nærum · Denmark Telephone: +45 7741 2000 · Fax: +45 4580 1405 · www.bksv.com · info@bksv.com

Local representatives and service organisations worldwide



BN 0797 – 11